

XP-233B

Thermal Barcode Printer

- Various label width, can be 20mm-60mm
- Label paper auto detection
- Temperature control function
- Modularity design and meet with various applications
- Support QR CODE Printing and Bluetooth

Xprinter®



Coffee Shop



Shopping




Mart



XP-233B

Thermal Barcode Printer



Model XP-233B		
Mode	Label print mode	Receipt print mode
Printing Features		
Resolution	203 DPI	
Printing method	Direct Thermal	
Print speed	50.8~101 mm/s Max.	90 mm/s Max.
Print width	Max 56 mm	48mm
Media		
Media type	Thermal stickers paper/ adhesive paper	Paper End, Cover Open
Media width	20~60 mm	58mm
Media thickness	0.06 ~ 0.08 mm	
Media roll diameter	Max.100 mm	
Performance Features		
Input buffer	4096 Kbytes	4096 Kbytes
NV flash	4096 Kbytes	4096 Kbytes
Interfaces	USB/USB+Serial/USB+Bluetooth	
Sensors	Paper End, Cover Open, Gap	Paper End, Cover Open
Drawer port	1 ports (Pin 2 for cashdrawer)	
Fonts/Graphics/Symbologies		
Character	Font 0 to Font8	Font A: 12x24, Font B: 9x17, CHN: 24*24
1D barcode	CODE128, EAN128, ITF, CODE39, CODE39C, CODE39S, CODE93, EAN13, EAN13+2, EAN13+5, EAN8, EAN8+2, EAN8+5, CODABAR, POSTNET, UPC-A, UPCA+2, UPCA+5, UPCE, UPCE+2, UPCE+5, MSI, MSIC, PLESSEY, ITF14, EAN14	Coda Bar, Code 39, Code 93, Code 128, EAN-8, EAN-13, ITF, UPC-A, UPC-E
2D bar code	QRCODE, PDF417, Data Matrix	
Emulaion	TSPL	ESC/POS
Physical Features		
Dimension	190 x 135 x 137mm (D×W×H)	
Weight	1.18 kg	
Reliability		
Print head life	50 km	
Software		
Driver	Windows	Windows/ Linux/ Mac/ Android
SDK	iOS/ Android/ Windows	
Power supply		
Input	100-240V 50/60H	
Output	DC 12V/3A	
Environmental Conditions		
Operation	5~45 °C; 20 ~ 80%RH	
Storage environment	-40 ~ 55°C; ≤93%RH	