

XP-Q361U

Thermal Barcode Printer

Xprinter®

XP-Q361U

Thermal Barcode Printer



Receipt &
label printer
with fashionable
design



Label mode

Receipt mode



- Support both receipt printing and label printing



- Support missing paper alarm function



- Paper roll diameter: 80mm Max.



- Support IAP online upgrade



- Support QR CODE, PDF417 DataMatrix



- Multiple interface



www.x-printer.gr

Model		XP-Q361U	
Print mode	Label print mode		Receipt print mode
Printing method	Direct Thermal		
Resolution	203 DPI		
Max.print speed	127 mm/s Max.		180 mm/s
Max.print width	76 mm		
RAM	4M		
Flash	4M		
Interfaces	USB / USB+Lan / USB+Serial+Lan (Optional: USB+WiFi / USB+Bluetooth)		
Print head temperature detection	Thermistor		
Print head position detection	Micro Switch		
Media			
Media type	Thermal Label Sticker Paper		Thermal Paper roll
Media width	20~80mm		
Media roll diameter	80 mm		
Media inner diameter	25mm~38mm		
Paper taken method	Tearing off		
Media thickness	0.06 ~ 0.19 mm		
Fonts/Graphics/Symbologies			
1D barcode	CODE128 / 128M / EAN128 / CODE39 / 39C / 39S / CODE93 / EAN13 / EAN13+2 / EAN13+5 / EAN8 / EAN8+2 / EAN8+5 / 25 / 25C / CODABAR / POSTNET / UPC-A / UPCA+2 / UPCA+5 / UPC-E / UPCE+2 / UPC-E+5 / CPOST / MSI / MSIC / PLESSEY / ITF14 / EAN14		UPC-A/UPC-E/JAN13(EAN13)/ JAN8(EAN8)/CODE39/ITF/ CODABAR/CODE93/CODE128
2D bar code	PDF417、QRCODE、DataMatrix		QR code
Character sizes	FONT 1 to FONT 8 、K、TST24.BF2、TSS24.BF2		Font A:1.5mm×3.0mm(12×24 dots) Font B:1.1mm×2.1mm(9×17 dots) Chinese:3.0mm×3.0mm(24×24 dots)
Emulation	TSPL		ESC / POS
Physical Features			
Dimension	170.5 * 137.2 * 136.5 mm		
Weight	0.77 kg		
Operation	5 ~ 45℃, Humidity: 20 ~ 80%		
Storage environment	-40 ~ 55℃, Humidity: ≤93% (40℃)		
Power Input	DC 24V/2.5A		
Print head life	50 KM		
Operating system	WINDOWS/ Android / IOS		

