

XP-Q371U

Thermal Barcode Printer

Xprinter®

XP-Q371U

Thermal Barcode Printer



Model		XP-Q371U	
Print mode	Label print mode	Receipt print mode	
Printing method	Direct Thermal		
Resolution	203 DPI		
Max.print speed	127 mm/s Max.	180 mm/s	
Max.print width	76 mm		
RAM	4M		
Flash	4M		
Interfaces	USB / USB+Lan / USB+Serial+Lan (Optional: WiFi / Bluetooth)		
Print head temperature detection	Thermistor		
Print head position detection	Micro Switch		
Media			
Media type	Thermal roll paper, thermal adhesive paper		
Media width	20~80mm		
Media roll diameter	Max.83 mm		
Media inner diameter	25mm~38mm		
Paper exit method	Tearing off		
Media thickness	0.06 ~ 0.19 mm		
Fonts/Graphics/Symbologies			
1D barcode	CODE128 / EAN128 / ITF / CODE39 / CODE39C / CODE39S / CODE93 / EAN13 / EAN13+2 / EAN13+5 / EAN8 / EAN8+2 / EAN8+5 / CODABAR / POSTNET / UPC-A/ UPCA+2 /UPCA+5/ UPCE / UPCE+2 / UPCE+5 / MSI / MSIC / PLESSEY /ITF14 / EAN14		
2D bar code	PDF417、QRCODE、DataMatrix		
Character sizes	Commonly used in single-byte fonts; FONT 1 to FONT 8, K, TST24.BF2,TSS24.BF2		
Emulation	TSPL	ESC / POS	
Physical Features			
Dimension	183*140*132.5mm		
Weight	0.9 kg		
Operation	5~45 °C, Humidity:RH 10 ~ 80%		
Storage environment	-40 ~ 55 °C, Humidity:93% RH		
Power Input	DC 24V/2.5A		
Print head life	50 KM		
Operating system	WINDOWS/ Android / IOS		



- Support both receipt printing and label printing

- Support missing paper alarm function

- Support IAP online upgrade



POWER D/K



USB



+

- Multiple interface,
USB / USB+Lan / USB+Serial+Lan
(Optional: WIFI / Bluetooth)



www.x-printer.gr

